

INSTALLATION INSTRUCTIONS

Flexi Top

Helmut Seitz GMBH
Kfz.-Produkte

Joseph-Baur-Str. 4
+49 (0)821/54 38 62-0
+49 (0)821/54 38 62-99

DE-86316 Friedberg
www.helmut-seitz.de
info@helmut-seitz.de

FOR WORKSHOP USE ONLY

Attach the holder to the vehicle with ring washers (Ø 20 mm diameter) using the existing drill holes.

Notice:

The user is responsible on his own for the correct and professional installation. Especially detection angles of vehicle cameras and sensors must not be affected. Please ask us for alternatives in case of problems with limited space.

Illustration 1 - Insert the sign

Insert the sign (in direction of arrow 1) from the bottom up under the top edge of the baseplate. Press the plate into the center holding clamp (in direction of arrow 2). The sign is held now.

Tipp: Pre-Curve the license plate first to optimize the fit for curved vehicle fronts.



Illustration 1

Illustration 2 - Closing

Attention!

Bend the bar gently and push the left and right end in the baseplate. Then press the bar from the left and right side towards the middle into the baseplate, so that it **locks with hearable "click" sounds**.

The installation of the sign is completed.



Illustration 2

Illustration 3a and 3 b - Deinstallation

Insert the opening tool (or a screwdriver) in the middle of the advertising bar between the sign and the bar, until the bar is unlocked and spread open. Then take the bar in the middle and pull it carefully out of the baseplate (in direction of arrow).

Remove the license plate out of the holding clamp by using our opening tool.



Illustration 3a

Opening tool
(partial view)



Illustration 3b